**Full Paper** Reference Object Identifier – ROI: jbc-01/18-55-8-46 The Digital Object Identifier - DOI: 10.37952/ROI-jbc-01/18-55-8-46 Submitted on May 06, 2018.

## **Physical-mechanical properties of cellulose-fibrous** materials and the influence on them of the y-radiation

© Ludmila S. Kocheva,<sup>1,3</sup> Anatoly P. Karmanov,<sup>2,3</sup>\*<sup>+</sup> and Ida I. Shuktomova<sup>4</sup>

<sup>1</sup>Chemistry Mineral Raw Material Laboratory. Institute of Geology of the Komi Science Center of the Ural Branch of the Russian Academy of Sciences. Pervomajskaja St., 54. Syktyvkar, 167982. Komi Republic. Russia. Phone: +7 (8212) 24-54-16. E-mail: lskocheva@geo.komisc.ru

<sup>2</sup> Biochemistry and Biotechnology Laboratory. Institute of Biology, Komi Scientific Center, Ural Division, Russian Academy of Sciences. Kommunisticheskaya St., 28. Syktyvkar, 167982. Komi Republic. Russia.

Phone: +7 (909) 120-81-63. E-mail: apk0948@ib.komisc.ru

<sup>3</sup> Chemistrv Department. Pitirim Sorokin Syktyvkar State University. Oktiabrskii Av., 55. Syktyvkar. 167001. Komi Republic. Russia.

<sup>4</sup>Radionuclides migration and radiochemistry Laboratory. Institute of Biology, Komi Scientific Center, Ural Division, Russian Academy of Sciences. Kommunisticheskaja, 28, Syktyvkar, 167982. Komi Republik. Russia. Phone: +7 (8212) 24-01-63. E-mail: shuktomovaii@ib.komisc.ru

\*Supervising author; <sup>+</sup>Corresponding author

*Keywords:* cellulose,  $\gamma$ -irradiation, IR-spectroscopy, cellulose-fibrous materials, the mechanical strength of the paper, aging the paper.

## Abstract

Work presents the results of investigating the influence of  $\gamma$ -irradiation on the physical-mechanical properties of cellulose-fibrous materials. It are used fibrous semifinished products - sulfate bleached coniferous cellulose, thermomechanical mass, and also compositions of paper pulp on their basis, which include kaolin, rosin glue and coagulant-precipitator (sulfate alumina and sulfate of titanyl and ammonium  $(NH_4)_2TiO(SO_4)_2H_2O)$ . It is shown that the replacement of the industrially utilized sulfate alumina to the water-soluble salt of titanium(IV) contributes to an increase in the indices of mechanical strength and radiation durability of the paper preparates. Thus, breaking length and to the resistance to tear of paper afterward  $\gamma$ -irradiation practically in 2 time exceeds this index for the nonirradiated model. During the study of interaction of cellulose with sulfate of titanyl and ammonium it is established that maximum interaction of cellulose with salt of titanium(IV), which undergoing in the aqueous solutions the complex processes of hydrolysis and polymerization, is observed in the range 3.55 > pH < 6.2. Changes in the IR-spectra of the irradiated cellulose before and after of modification by salt of titanium(IV) testify about regrouping of the system of hydrogenous bonds and possibility of the formation of new terminal bonds, which positively affects the strength characteristics of cellulose fibers. For the irradiated modified cellulose are characteristic an increase in the expanded surface and the increased fibrillation of fibers, which contributes to an increase in the cohesive forces of the fibers between themselves.

## References

- [1] V.S. Sukhanov. O povyshenii effektivnosti raboti SBP za schet snigeniya zatrat na proizvodstvo sirya (On improving of the effectiveness of the CPP by lowering the cost of production of raw materials). Lesprom-inform. 2005. No.3. Vol.25. P.60-64. (russian)
- [2] E.R. Mullina, E.G. Lygina, O.V. Ershova, K.V. Pinchukova. Issledovanie vliyaniya kchimicheskogo sostava sellulozi na phisiko-mechanicheskie svoistva bumagi (Research of influence of chemical composition of pulp on the physico-mechanical properties of paper). Modern High Technologies. 2015. No.9. P.56-58. (russian)
- [3] M. Montazer, E. Pakdel, V.B. Moghadam. Nano titanium gioxide on wool keratin as UV absorber stabilized by butane tetra carboxylic acid (BTCA): a statistical prospect. *Fibers and Polymers*.2010. Vol.11. No.7. P.967-975.
- [4] Ch.-Ch. Wang, Ch.-Ch. Chen. Physical properties of crosslinked cellulose catalyzed with nano titanium gioxide. Journal of Applied Polymer Science. 2005. Vol.97. P.2450-2456.
- [5] Production of cellulose, wood pulp, paper and cardboard. Information and technical reference for best available technologies. ITS 1-2015. Moscow: Buro NDT. 2015. 465p. (russian)

<sup>46 ©</sup> *Butlerov Communications.* 2018. Vol.55. No.8. Kazan. The Republic of Tatarstan. Russia.

PHYSICAL-MECHANICAL PROPERTIES OF CELLULOSE-FIBROUS MATERIALS AND THE INFLUENCE... 46-52

- [6] V.F. Klepikov. Nuclear reactions, technology of modification and analysis of materials. East European Journal of Advanced Technology. 2012. No.2(5). P.37-43. (russian)
- [7] M.L. Kerber. Polymer composite materials. Struktura. Svoistva. Technologii. *St. Petersburg:* Professiya.2008. 560p. (russian)